

Chemray 120

Auto Chemistry Analyzer



Technical Specifications

System Function

- Throughput: up to 100 tests per hour
- Contents of testing: Clinical chemistry, Immunoturbidimetric
- Analytical modes: End-point, Two-point, Kinetic
- Programming: Open system with user defined programs
- Automatic, Random Access
- STAT sample priority

Sample Tray

- Sample position: 9 positions for samples
- Sample volume: 3 ~ 45 μL , 0.1 μL adjustable
- Any position for standard and quality control setting

Reagent Tray

- Reagent position: 26 positions for reagents
- Reagent volume
 - R1: 180 ~ 450 μL , 0.1 μL adjustable
 - R2: 3 ~ 450 μL , 0.1 μL adjustable

Reaction Tray

- Reaction positions: 90 cuvettes, 10 cuvettes/strip
- Cuvette: Optical length 5mm
- Reaction volume: 180 ~ 500ul
- Reaction temperature: 37°C

Probe

- Pre-heating for reagent
- Collision protection, Liquid level detection and Inventory checking
- Automatic inner and outer probe washing after every cycle

Print out

- Built-in thermal printer, external printer optional

Measuring and Optic System


- Lamp: Halogen lamp
- Absorbance range: 0 ~ 3.500Abs
- Wavelengths: 8 wavelengths from 320-850nm
- Resolution: 0.0001ABS

Working Condition

- Power supply: 100-240 VAc 50/60 Hz
- Temperature: 10 ~ 35°C
- Humidity: 35 ~ 80%
- Water consumption: <3 L/hour
- Dimension L×W×H(mm): 630×480×510
- Net weight: 70 KG



Status Menu



QC Graph

